

10/685,787

PATENT

AMENDMENT B (IN RESPONSE TO PAPER NO. 20050419
(OFFICE ACTION DATED JUNE 24, 2005))

CLAIMS

1. (ORIGINAL) An apparatus including data signal amplification and processing circuitry with multiple signal gains, comprising:

a signal node to convey an input signal having an input signal value;
amplification circuitry coupled to said signal node, including a variable signal gain responsive to at least one gain control signal having a plurality of values, and responsive to said input signal by providing an intermediate signal having a plurality of values corresponding to said plurality of gain control signal values;

sampling circuitry coupled to said amplification circuitry and responsive to a sampling control signal by sampling said intermediate signal to provide a sample signal having a plurality of values which include at least a maximum and a minimum, and correspond to said plurality of intermediate signal values; and

processing circuitry coupled to said sampling circuitry and responsive to one or more processing control signals by processing said sample signal to provide a processed signal having a value corresponding to said input signal value, wherein said processed signal value represents

said maximum sample signal value when said maximum value fails to traverse a predetermined lower threshold,

said minimum sample signal value when an adjacent larger one of said plurality of sample signal values traverses a predetermined higher threshold,

a smaller of mutually adjacent ones of a pair of said plurality of sample signal values when a larger one of said pair of sample signal values traverses said predetermined higher threshold and said smaller value fails to traverse said predetermined lower threshold, and

a combination of said smaller and larger ones of said pair of sample signal values when said larger value traverses said predetermined lower threshold

Att. Docket No.: 03-019-US (10101.03.0190) - 2 -
CHICAGO/#1390143.1

10/685,787

PATENT

AMENDMENT B (IN RESPONSE TO PAPER NO. 20050419
(OFFICE ACTION DATED JUNE 24, 2005))

and fails to traverse said predetermined higher threshold.

2. (ORIGINAL) The apparatus of claim 1, wherein said amplification circuitry comprises:

amplifier circuitry including input and output terminals; and
a variable feedback capacitance coupled between said amplifier circuitry input and output terminals and responsive to one or more of said at least one gain control signal.

3. (ORIGINAL) The apparatus of claim 1, wherein said amplification circuitry comprises:

first amplifier circuitry including input and output terminals;
a feedback capacitance coupled between said first amplifier circuitry input and output terminals; and
second amplifier circuitry coupled to said first amplifier circuitry output terminal and having said variable signal gain responsive to said at least one gain control signal.

4. (ORIGINAL) The apparatus of claim 1, wherein said amplification circuitry comprises:

amplifier circuitry including input and output terminals;
a feedback capacitance coupled between said amplifier circuitry input and output terminals; and
switched circuitry coupled across said feedback capacitance and including a resistance and a switch responsive to one or more of said at least one gain control signal.

5. (ORIGINAL) The apparatus of claim 1, wherein:

Atty. Docket No.: 03-019-US (10101.03.0190) - 3 -
CHICAGO/#1390143.1

10/685,787

PATENT

AMENDMENT B (IN RESPONSE TO PAPER NO. 20050419
(OFFICE ACTION DATED JUNE 24, 2005))

said input signal has an input signal charge associated therewith; and
said amplification circuitry comprises
capacitive circuitry, and
a switch coupled between said signal node and said capacitive
circuitry, and responsive to one or more of said at least one gain control signal by
conveying a predetermined portion of said input signal charge to said capacitive
circuitry.

6. *(PREVIOUSLY PRESENTED)* The apparatus of claim 1, wherein
said sampling circuitry comprises:

serial switching circuitry coupled to said amplification circuitry and
responsive to said sampling control signal by providing a switched signal path for
said intermediate signal; and

shunt capacitive circuitry coupled to said serial switching circuitry and
responsive to said intermediate signal by charging to provide said sample signal.

7. *(ORIGINAL)* The apparatus of claim 1, wherein said processing
circuitry comprises:

analog-to-digital conversion circuitry responsive to one of said one or more
processing control signals by converting said sample signal to provide a digital
signal having a plurality of values corresponding to said plurality of sample signal
values; and

computational circuitry coupled to said analog-to-digital conversion
circuitry and responsive to another one or more of said one or more processing
control signals and said digital signal by providing said processed signal.

8. *(ORIGINAL)* The apparatus of claim 7, wherein said computational
circuitry comprises:

Atty. Docket No.: 03-019-US (10101.03.0190) - 4 -
CHICAGO/#1390143.1

10/685,787

PATENT

AMENDMENT B (IN RESPONSE TO PAPER NO. 20050419
(OFFICE ACTION DATED JUNE 24, 2005))

comparison circuitry responsive to said digital signal by comparing said plurality of digital signal values to said predetermined lower and higher thresholds; and

combining circuitry responsive to said digital signal by selectively combining first and second ones of said plurality of digital signal values to provide a combination signal corresponding to said combination of said first and second ones of said plurality of sample signal values.

9. (ORIGINAL) An apparatus including data signal amplification and processing circuitry with multiple signal gains, comprising:

amplifier means, including variable signal gain, for receiving an input signal having an input signal value and at least one gain control signal having a plurality of values, and in response thereto generating an intermediate signal having a plurality of values corresponding to said plurality of gain control signal values;

sampling means for receiving a sampling control signal and in response thereto sampling said intermediate signal and generating a sample signal having a plurality of values which include at least a maximum and a minimum, and correspond to said plurality of intermediate signal values; and

processor means for receiving one or more processing control signals and in response thereto processing said sample signal and generating a processed signal having a value corresponding to said input signal value, wherein said processed signal value represents

said maximum sample signal value when said maximum value fails to traverse a predetermined lower threshold,

said minimum sample signal value when an adjacent larger one of said plurality of sample signal values traverses a predetermined higher threshold,

a smaller of mutually adjacent ones of a pair of said plurality of

Att. Docket No.: 03-019-US (10101.03.0190) - 5 -
CHICAGO/#1390143.1

10/685,787

PATENT

AMENDMENT B (IN RESPONSE TO PAPER NO. 20050419
(OFFICE ACTION DATED JUNE 24, 2005))

sample signal values when a larger one of said pair of sample signal values traverses said predetermined higher threshold and said smaller value fails to traverse said predetermined lower threshold, and

a combination of said smaller and larger ones of said pair of sample signal values when said larger value traverses said predetermined lower threshold and fails to traverse said predetermined higher threshold.

10. (ORIGINAL) A method of data signal amplification and processing with multiple signal gains, comprising:

receiving an input signal having an input signal value;

receiving at least one gain control signal having a plurality of values;

generating, in response to said input signal and said at least one gain control signal, an intermediate signal having a plurality of values corresponding to said plurality of gain control signal values;

receiving a sampling control signal and in response thereto sampling said intermediate signal and generating a sample signal having a plurality of values which include at least a maximum and a minimum, and correspond to said plurality of intermediate signal values; and

receiving one or more processing control signals and in response thereto processing said sample signal and generating a processed signal having a value corresponding to said input signal value, wherein said processed signal value represents

said maximum sample signal value when said maximum value fails to traverse a predetermined lower threshold,

said minimum sample signal value when an adjacent larger one of said plurality of sample signal values traverses a predetermined higher threshold,

a smaller of mutually adjacent ones of a pair of said plurality of sample signal values when a larger one of said pair of sample signal values

Atty. Docket No.: 03-019-US (10101.03.0190) - 6 -
CHICAGO/#1390143.1

10/685,787

PATENT

AMENDMENT B (IN RESPONSE TO PAPER NO. 20050419
(OFFICE ACTION DATED JUNE 24, 2005))

traverses said predetermined higher threshold and said smaller value fails to traverse said predetermined lower threshold, and
a combination of said smaller and larger ones of said pair of sample signal values when said larger value traverses said predetermined lower threshold and fails to traverse said predetermined higher threshold.

11. *(ORIGINAL)* The method of claim 10, wherein said generating, in response to said input signal and said at least one gain control signal, an intermediate signal having a plurality of values corresponding to said plurality of gain control signal values comprises:

controlling a variable feedback capacitance with said at least one gain control signal; and

generating said intermediate signal as a function of said input signal and said controlled variable feedback capacitance.

12. *(PREVIOUSLY PRESENTED)* The method of claim 10, wherein said generating, in response to said input signal and said at least one gain control signal, an intermediate signal having a plurality of values corresponding to said plurality of gain control signal values comprises:

generating an initial signal in response to said input signal with first amplifier circuitry including a feedback capacitance; and

generating said intermediate signal in response to said initial signal with second amplifier circuitry having a variable signal gain responsive to said at least one gain control signal.

13. *(ORIGINAL)* The method of claim 10, wherein said generating, in response to said input signal and said at least one gain control signal, an intermediate signal having a plurality of values corresponding to said plurality of

Att. Docket No.: 03-019-US (10101.03.0190) - 7 -
CHICAGO/#1390143.1

10/685,787

PATENT

AMENDMENT B (IN RESPONSE TO PAPER NO. 20050419
(OFFICE ACTION DATED JUNE 24, 2005))

gain control signal values comprises:

selectively discharging a feedback capacitance with said at least one gain control signal; and

generating said intermediate signal as a function of said input signal and said selectively discharged feedback capacitance.

14. (ORIGINAL) The method of claim 10, wherein:

said input signal has an input signal charge associated therewith; and

said generating, in response to said input signal and said at least one gain control signal, an intermediate signal having a plurality of values corresponding to said plurality of gain control signal values comprises conveying a predetermined portion of said input signal charge, responsive to one or more of said at least one gain control signal, to capacitive circuitry.

15. (ORIGINAL) The method of claim 10, wherein said receiving a sampling control signal and in response thereto sampling said intermediate signal and generating a sample signal having a plurality of values corresponding to said plurality of intermediate signal values comprises:

responding to said sampling control signal by providing a switched signal path for said intermediate signal; and

responding to said intermediate signal by charging shunt capacitive circuitry to provide said sample signal.

16. (ORIGINAL) The method of claim 10, wherein said receiving one or more processing control signals and in response thereto processing said sample signal and generating a processed signal having a value corresponding to said input signal value comprises:

responding to one of said one or more processing control signals by

Any. Docket No.: 03-019-US (10101.03.0190) - 8 -
CHICAGO/#1390143.1

10/685,787

PATENT

AMENDMENT B (IN RESPONSE TO PAPER NO. 20050419
(OFFICE ACTION DATED JUNE 24, 2005))

converting said sample signal to a digital signal having a plurality of values corresponding to said plurality of sample signal values; and
responding to another one or more of said one or more processing control signals and said digital signal by generating said processed signal.

17. (ORIGINAL) The method of claim 16, wherein said responding to another one or more of said one or more processing control signals and said digital signal by generating said processed signal comprises:

responding to said digital signal by comparing said plurality of digital signal values to said predetermined lower and higher thresholds; and

responding to said digital signal by selectively combining first and second ones of said plurality of digital signal values to generate a combination signal corresponding to said combination of said first and second ones of said plurality of sample signal values.

18. (CURRENTLY AMENDED) An apparatus including data signal amplification and processing circuitry with multiple signal gains, comprising:

signal acquisition circuitry responsive to an image data signal by providing an acquired data signal;

amplification circuitry coupled to said signal acquisition circuitry and responsive to at least one gain control signal and said acquired data signal by amplifying said acquired data signal with a plurality of signal gains to produce a corresponding plurality of amplified data signals;

sampling circuitry coupled to said amplification circuitry and responsive to at least one sampling control signal and said plurality of amplified data signals by sampling said plurality of amplified data signals to produce a corresponding plurality of sampled data signals having a like plurality of values which include at least a maximum and a minimum, and correspond to said plurality of amplified

Att. Docket No.: 03-019-US (10101.03.0190) - 9 -
CHICAGO/#1390143 .1

10/685,787

PATENT

AMENDMENT B (IN RESPONSE TO PAPER NO. 20050419
(OFFICE ACTION DATED JUNE 24, 2005))

data signals; and

processing circuitry coupled to said sampling circuitry and responsive to one or more ~~criteria~~ reference signals and one or more of said plurality of sampled data signals by providing a data output signal corresponding to

said maximum sampled data signal value when said maximum value fails to satisfy a first one of a plurality of criteria related to said one or more reference signals,

said minimum sampled data signal value when an adjacent larger one of said plurality of sampled data signal values satisfies a second one of said plurality of criteria,

a smaller of mutually adjacent ones of a pair of said plurality of sampled data signal values when a larger one of said pair of sampled data signal values satisfies said second one of said plurality of criteria and said smaller value fails to satisfy said first one of said plurality of criteria, and

a combination of said smaller and larger ones of said pair of sampled data signal values when said larger value satisfies said first one of said plurality of criteria and fails to satisfy said second one of said plurality of criteria.

19. (ORIGINAL) The apparatus of claim 18, wherein said amplification circuitry comprises:

amplifier circuitry including input and output terminals; and

a variable feedback capacitance coupled between said amplifier circuitry input and output terminals and responsive to one or more of said at least one gain control signal.

20. (PREVIOUSLY PRESENTED) The apparatus of claim 18, wherein said amplification circuitry comprises:

first amplifier circuitry including input and output terminals;

Atty. Docket No.: 03-019-US (10101.03.0190)- 10 -
CHICAGO/#1390143.1

10/685,787

PATENT

AMENDMENT B (IN RESPONSE TO PAPER NO. 20050419
(OFFICE ACTION DATED JUNE 24, 2005))

a feedback capacitance coupled between said first amplifier circuitry input and output terminals; and

second amplifier circuitry coupled to said first amplifier circuitry output terminal and having a variable signal gain responsive to said at least one gain control signal.

21. (ORIGINAL) The apparatus of claim 18, wherein said amplification circuitry comprises:

amplifier circuitry including input and output terminals;

a feedback capacitance coupled between said amplifier circuitry input and output terminals; and

switched circuitry coupled across said feedback capacitance and including a resistance and a switch responsive to one or more of said at least one gain control signal.

22. (ORIGINAL) The apparatus of claim 18, wherein:

said input signal has an input signal charge associated therewith; and

said amplification circuitry comprises

capacitive circuitry, and

a switch coupled between said signal node and said capacitive circuitry, and responsive to one or more of said at least one gain control signal by conveying a predetermined portion of said input signal charge to said capacitive circuitry.

23. (PREVIOUSLY PRESENTED) The apparatus of claim 18, wherein said sampling circuitry comprises:

serial switching circuitry coupled to said amplification circuitry and responsive to said sampling control signal by providing a switched signal path for

Atty. Docket No.: 03-019-US (10101.03.0190)- 11 -
CHICAGO/#1390143.1

10/685,787

PATENT

AMENDMENT B (IN RESPONSE TO PAPER NO. 20050419
(OFFICE ACTION DATED JUNE 24, 2005))

said intermediate signal; and

shunt capacitive circuitry coupled to said serial switching circuitry and responsive to said intermediate signal by charging to provide said sample signal.

24. *(ORIGINAL)* The apparatus of claim 18, wherein said processing circuitry comprises:

analog-to-digital conversion circuitry responsive to one of said one or more processing control signals by converting said sample signal to provide a digital signal having a plurality of values corresponding to said plurality of sample signal values; and

computational circuitry coupled to said analog-to-digital conversion circuitry and responsive to another one or more of said one or more processing control signals and said digital signal by providing said processed signal.

25. *(ORIGINAL)* The apparatus of claim 24, wherein said computational circuitry comprises:

comparison circuitry responsive to said digital signal by comparing said plurality of digital signal values to said predetermined lower and higher thresholds; and

combining circuitry responsive to said digital signal by selectively combining first and second ones of said plurality of digital signal values to provide a combination signal corresponding to said combination of said first and second ones of said plurality of sample signal values.

26. *(CURRENTLY AMENDED)* An apparatus including data signal amplification and processing circuitry with multiple signal gains, comprising:

signal acquisition means for acquiring a data signal;

amplifier means for amplifying said acquired data signal with a plurality of

Att'y. Docket No.: 03-019-US (10101.03.0190)- 12 -
CHICAGO/#1390143-1

10/685,787

PATENT

AMENDMENT 8 (IN RESPONSE TO PAPER NO. 20050419
(OFFICE ACTION DATED JUNE 24, 2005))

signal gains and generating a corresponding plurality of amplified data signals;

sampling means for sampling said plurality of amplified data signals and generating a corresponding plurality of sampled data signals having a like plurality of values which include at least a maximum and a minimum, and correspond to said plurality of amplified data signals; and

processor means for receiving one or more reference signals, processing one or more of said plurality of sampled data signals and generating a data output signal corresponding to

said maximum sampled data signal value when said maximum value fails to satisfy a first one of a plurality of criteria related to said one or more reference signals,

said minimum sampled data signal value when an adjacent larger one of said plurality of sampled data signal values satisfies a second one of said plurality of criteria,

a smaller of mutually adjacent ones of a pair of said plurality of sampled data signal values when a larger one of said pair of sampled data signal values satisfies said second one of said plurality of criteria and said smaller value fails to satisfy said first one of said plurality of criteria, and

a combination of said smaller and larger ones of said pair of sampled data signal values when said larger value satisfies said first one of said plurality of criteria and fails to satisfy said second one of said plurality of criteria.

27. *(CURRENTLY AMENDED)* A method of data signal amplification and processing with multiple signal gains, comprising:

acquiring an image data signal;

amplifying said image data signal with a plurality of signal gains to produce a corresponding plurality of amplified data signals;

sampling said plurality of amplified data signals to produce a

Atty. Docket No.: 03-019-US (10101.03.0190)- 13 -
CHICAGO/#1390143.1

10/685,787

PATENT

AMENDMENT B (IN RESPONSE TO PAPER NO. 20050419
(OFFICE ACTION DATED JUNE 24, 2005))

corresponding plurality of sampled data signals having a like plurality of values which include at least a maximum and a minimum, and correspond to said plurality of amplified data signals;

comparing one or more of said plurality of sampled data signal values to one or more of a plurality of criteria reference signals; and

providing a data output signal corresponding to

said maximum sampled data signal value when said maximum value fails to satisfy a first one of said a plurality of criteria related to said one or more reference signals,

said minimum sampled data signal value when an adjacent larger one of said plurality of sampled data signal values satisfies a second one of said plurality of criteria,

a smaller of mutually adjacent ones of a pair of said plurality of sampled data signal values when a larger one of said pair of sampled data signal values satisfies said second one of said plurality of criteria and said smaller value fails to satisfy said first one of said plurality of criteria, and

a combination of said smaller and larger ones of said pair of sampled data signal values when said larger value satisfies said first one of said plurality of criteria and fails to satisfy said second one of said plurality of criteria.

28. (ORIGINAL) The method of claim 27, wherein said amplifying said image data signal with a plurality of signal gains to produce a corresponding plurality of amplified data signals comprises:

controlling a variable feedback capacitance; and

generating said plurality of amplified data signals as a function of said image data signal and said controlled variable feedback capacitance.

29. (ORIGINAL) The method of claim 27, wherein said amplifying

Atty. Docket No.: 03-019-US (10101.03.0190)- 14 -
CHICAGO/#1390143.1

10/685,787

PATENT

AMENDMENT B (IN RESPONSE TO PAPER NO. 20050419
(OFFICE ACTION DATED JUNE 24, 2005))

said image data signal with a plurality of signal gains to produce a corresponding plurality of amplified data signals comprises:

generating an initial signal in response to said image data signal with first amplifier circuitry including a feedback capacitance; and

generating said plurality of amplified data signals in response to said initial signal with second amplifier circuitry having said plurality of signal gains.

30. (ORIGINAL) The method of claim 27, wherein said amplifying said image data signal with a plurality of signal gains to produce a corresponding plurality of amplified data signals comprises:

selectively discharging a feedback capacitance; and

generating said plurality of amplified data signals as a function of said image data signal and said selectively discharged feedback capacitance.

31. (ORIGINAL) The method of claim 27, wherein:

said image data signal has a signal charge associated therewith; and

said amplifying said image data signal with a plurality of signal gains to produce a corresponding plurality of amplified data signals comprises conveying a plurality of predetermined portions of said image data signal charge to capacitive circuitry.

32. (ORIGINAL) The method of claim 27, wherein said sampling said plurality of amplified data signals to produce a corresponding plurality of sampled data signals having a like plurality of values which include at least a maximum and a minimum, and correspond to said plurality of amplified data signals comprises:

switching said plurality of amplified data signals; and

charging shunt capacitive circuitry with said switched plurality of amplified data signals to generate said plurality of sampled data signals.

Att. Docket No.: 03-019-US (10101.03.0190)- 15 -
CHICAGO/#1390143.1

10/685,787

PATENT

AMENDMENT B (IN RESPONSE TO PAPER NO. 20050419
(OFFICE ACTION DATED JUNE 24, 2005))

33. *(CURRENTLY AMENDED)* The method of claim 27, wherein said comparing one or more of said plurality of sampled data signal values to one or more of ~~a plurality of criteria reference signals~~ comprises comparing one or more of said plurality of sampled data signal values to one or more of a plurality of reference signals corresponding to predetermined lower and higher thresholds.

34. *(ORIGINAL)* The method of claim 27, wherein said providing a data output signal corresponding to a combination of said smaller and larger ones of said pair of sampled data signal values when said larger value satisfies said first one of said plurality of criteria and fails to satisfy said second one of said plurality of criteria comprises selectively combining a portion of said plurality of sampled data signal values.

35. *(CANCELLED)*

36. *(CURRENTLY AMENDED)* ~~The apparatus of claim 35, An~~
apparatus including data signal amplifier circuitry with multiple signal gains,
comprising:
_____ sampling amplifier circuitry responsive to at least one control signal and an
input signal having an input signal value by providing at least one sample signal
having a plurality of sample signal values, including maximum and minimum
sample signal values, and corresponding to said input signal value; and
_____ processing circuitry coupled to said sampling amplifier circuitry and
responsive to said at least one sample signal and one or more processing control
signals by processing said at least one sample signal to provide a processed signal
having a value corresponding to said input signal value;
_____ wherein said processed signal value represents:

Att. Docket No.: 03-019-US (10101.03.0190)- 16 -
CHICAGO/#1390143.1

10/685,767

PATENT

AMENDMENT B (IN RESPONSE TO PAPER NO. 20050419
(OFFICE ACTION DATED JUNE 24, 2005))

said maximum sample signal value when said maximum value fails to traverse a predetermined lower threshold;

said minimum sample signal value when an adjacent larger one of said plurality of sample signal values traverses a predetermined higher threshold;

a smaller of mutually adjacent ones of a pair of said plurality of sample signal values when a larger one of said pair of sample signal values traverses said predetermined higher threshold and said smaller value fails to traverse said predetermined lower threshold; and

a combination of said smaller and larger ones of said pair of sample signal values when said larger value traverses said predetermined lower threshold and fails to traverse said predetermined higher threshold.

37. (CANCELLED)

38. (CURRENTLY AMENDED) ~~The apparatus of claim 35. An apparatus including data signal amplifier circuitry with multiple signal gains, comprising:~~

~~sampling amplifier circuitry responsive to at least one control signal and an input signal having an input signal value by providing at least one sample signal having a plurality of sample signal values, including maximum and minimum sample signal values, and corresponding to said input signal value; and~~

~~processing circuitry coupled to said sampling amplifier circuitry and responsive to said at least one sample signal and one or more processing control signals by processing said at least one sample signal to provide a processed signal having a value corresponding to said input signal value;~~

~~wherein said processed signal value represents one of a plurality of values which includes~~

~~said maximum sample signal value.~~

Attr. Docket No.: 03-019-US (10101.03.0190)- 17 -
CHICAGO/#1390143.1

10/685,787

PATENTAMENDMENT B (IN RESPONSE TO PAPER NO. 20050419
(OFFICE ACTION DATED JUNE 24, 2005))

said minimum sample signal value,
a first one of said plurality of sample signal values, and
a combination of said first one and a second one of said plurality of
sample signal values; and
_____ wherein said sampling amplifier circuitry comprises:
_____ first amplifier circuitry including input and output terminals;
_____ a feedback capacitance coupled between said first amplifier
circuitry input and output terminals; and
_____ second amplifier circuitry coupled to said first amplifier circuitry
output terminal and having said variable signal gain responsive to at least one of
said at least one control signal.

39. (CANCELLED)

40. (CURRENTLY AMENDED) ~~The apparatus of claim 35, An~~
apparatus including data signal amplifier circuitry with multiple signal gains,
comprising:
sampling amplifier circuitry responsive to at least one control signal and an
input signal having an input signal value by providing at least one sample signal
having a plurality of sample signal values, including maximum and minimum
sample signal values, and corresponding to said input signal value; and
processing circuitry coupled to said sampling amplifier circuitry and
responsive to said at least one sample signal and one or more processing control
signals by processing said at least one sample signal to provide a processed signal
having a value corresponding to said input signal value;
wherein said processed signal value represents one of a plurality of values
which includes
said maximum sample signal value.

Atty. Docket No.: 03-019-US (10101.03.0190)- 18 -
CHICAGO/#1390143.1

10/685,787

PATENT

AMENDMENT B (IN RESPONSE TO PAPER NO. 20050419
(OFFICE ACTION DATED JUNE 24, 2005))

said minimum sample signal value,
a first one of said plurality of sample signal values, and
a combination of said first one and a second one of said plurality of
sample signal values; and

wherein:

said input signal has an input signal charge associated therewith;
and

said sampling amplifier circuitry comprises
a signal node to convey said input signal,
capacitive circuitry, and
a switch coupled between said signal node and said
capacitive circuitry, and responsive to one or more of said at least one control
signal by conveying a predetermined portion of said input signal charge to said
capacitive circuitry.

41. *(CURRENTLY AMENDED)* ~~The apparatus of claim 35. An~~
apparatus including data signal amplifier circuitry with multiple signal gains,
comprising:

sampling amplifier circuitry responsive to at least one control signal and an
input signal having an input signal value by providing at least one sample signal
having a plurality of sample signal values, including maximum and minimum
sample signal values, and corresponding to said input signal value; and
processing circuitry coupled to said sampling amplifier circuitry and
responsive to said at least one sample signal and one or more processing control
signals by processing said at least one sample signal to provide a processed signal
having a value corresponding to said input signal value;

wherein said processed signal value represents one of a plurality of values
which includes

Atty. Docket No.: 03-019-US (10101.03.0190)- 19 -
CHICAGO/#1390143.1

10/685,787

PATENT

AMENDMENT B (IN RESPONSE TO PAPER NO. 20050419
(OFFICE ACTION DATED JUNE 24, 2005))

said maximum sample signal value,
said minimum sample signal value,
a first one of said plurality of sample signal values, and
a combination of said first one and a second one of said plurality of
sample signal values; and
_____ wherein said sampling amplifier circuitry comprises:
_____ serial switching circuitry responsive to one of said at least one
control signal by providing a switched signal; and
_____ shunt capacitive circuitry coupled to said serial switching circuitry
and responsive to said switched signal by charging to provide said at least one
sample signal.

42. (CANCELLED)

43. (CURRENTLY AMENDED) ~~The apparatus of claim 42, An~~
apparatus including data signal amplifier circuitry with multiple signal gains,
comprising:
_____ sampling amplifier circuitry responsive to at least one control signal and an
input signal having an input signal value by providing at least one sample signal
having a plurality of sample signal values, including maximum and minimum
sample signal values, and corresponding to said input signal value; and
_____ processing circuitry coupled to said sampling amplifier circuitry and
responsive to said at least one sample signal and one or more processing control
signals by processing said at least one sample signal to provide a processed signal
having a value corresponding to said input signal value;
_____ wherein said processed signal value represents one of a plurality of values
which includes
_____ said maximum sample signal value,

Atty. Docket No.: 03-019-US (10101.03.0190)- 20 -
CHICAGO/#1390143.1

10/685,787

PATENT

AMENDMENT B (IN RESPONSE TO PAPER NO. 20050419
(OFFICE ACTION DATED JUNE 24, 2005))

said minimum sample signal value,
a first one of said plurality of sample signal values, and
a combination of said first one and a second one of said plurality of
sample signal values;
wherein said processing circuitry comprises
analog-to-digital conversion circuitry responsive to one of said one
or more processing control signals by converting said sample signal to provide a
digital signal having a plurality of values corresponding to said plurality of sample
signal values, and
computational circuitry coupled to said analog-to-digital conversion
circuitry and responsive to another one or more of said one or more processing
control signals and said digital signal by providing said processed signal; and
wherein said computational circuitry comprises:
comparison circuitry responsive to said digital signal by comparing
said plurality of digital signal values to predetermined lower and higher thresholds;
thresholds, and
combining circuitry responsive to said digital signal by selectively
combining first and second ones of said plurality of digital signal values to provide
a combination signal corresponding to said combination of said first and second
ones of said plurality of sample signal values.

44. (CANCELLED)

45. (CANCELLED)

46. (CURRENTLY AMENDED) The method of claim 45. A method of
data signal amplification and processing with multiple signal gains, comprising:
receiving at least one control signal;
receiving an input signal having an input signal value;

Att. Docket No.: 03-019-US (10101.03.0190)- 21 -
CHICAGO/#1390143.1

10/685,787

PATENT

AMENDMENT B (IN RESPONSE TO PAPER NO. 20050419
(OFFICE ACTION DATED JUNE 24, 2005))

generating, in response to said at least one control signal and said input signal, at least one sample signal having a plurality of sample signal values, including maximum and minimum sample signal values, and corresponding to said input signal value; and

receiving one or more processing control signals and in response thereto processing said at least one sample signal and generating a processed signal having a value corresponding to said input signal value;

wherein said processed signal value represents one of a plurality of values which includes

said maximum sample signal value,

said minimum sample signal value,

a first one of said plurality of sample signal values, and

a combination of said first one and a second one of said plurality of sample signal values; and

wherein said processed signal value represents:

said maximum sample signal value when said maximum value fails to traverse a predetermined lower threshold;

said minimum sample signal value when an adjacent larger one of said plurality of sample signal values traverses a predetermined higher threshold;

a smaller of mutually adjacent ones of a pair of said plurality of sample signal values when a larger one of said pair of sample signal values traverses said predetermined higher threshold and said smaller value fails to traverse said predetermined lower threshold; and

a combination of said smaller and larger ones of said pair of sample signal values when said larger value traverses said predetermined lower threshold and fails to traverse said predetermined higher threshold.

47. (CANCELLED)

Atty. Docket No.: 03-019-US (10101.03.0190)- 22 -
CHICAGO/#1390143.1

10/685,787

PATENT

AMENDMENT B (IN RESPONSE TO PAPER NO. 20050419
(OFFICE ACTION DATED JUNE 24, 2005))

48. *(CURRENTLY AMENDED)* ~~The method of claim 45, wherein said~~
~~generating, in response to said at least one control signal and said input signal, at~~
~~least one sample signal having a plurality of sample signal values, including~~
~~maximum and minimum sample signal values, and corresponding to said input~~
~~signal value comprises: A method of data signal amplification and processing with~~
~~multiple signal gains, comprising:~~
~~_____ receiving at least one control signal;~~
~~_____ receiving an input signal having an input signal value;~~
~~_____ generating, in response to said at least one control signal and said input~~
~~signal, at least one sample signal having a plurality of sample signal values,~~
~~including maximum and minimum sample signal values, and corresponding to said~~
~~input signal value, by~~
~~_____ generating an initial signal in response to said input signal with first~~
~~amplifier circuitry including a feedback capacitance; capacitance, and~~
~~_____ generating said at least one sample signal in response to said initial~~
~~signal with second amplifier circuitry having a variable signal gain responsive to at~~
~~least one of said plurality control signals; signals; and~~
~~_____ receiving one or more processing control signals and in response thereto~~
~~processing said at least one sample signal and generating a processed signal having~~
~~a value corresponding to said input signal value;~~
~~_____ wherein said processed signal value represents one of a plurality of values~~
~~which includes~~
~~_____ said maximum sample signal value,~~
~~_____ said minimum sample signal value,~~
~~_____ a first one of said plurality of sample signal values, and~~
~~_____ a combination of said first one and a second one of said plurality of~~
~~sample signal values.~~

Atty. Docket No.: 03-019-US (10101.03.0190)- 23 -
CHICAGO/#1390143.1

10/685,787

PATENT

AMENDMENT B (IN RESPONSE TO PAPER NO. 20050419
(OFFICE ACTION DATED JUNE 24, 2005))

49. (CANCELLED)

50. (CURRENTLY AMENDED) ~~The method of claim 45, wherein:~~ A method of data signal amplification and processing with multiple signal gains, comprising:
receiving at least one control signal;
receiving an input signal having an input signal value, wherein
said input signal has an input signal charge associated therewith; and
said generating, in response to said at least one control signal and said input signal, at least one sample signal having a plurality of sample signal values, including maximum and minimum sample signal values, and corresponding to said input signal value, comprises by conveying a predetermined portion of said input signal charge, responsive to one or more of said at least one control signal, to capacitive circuitry; and
receiving one or more processing control signals and in response thereto processing said at least one sample signal and generating a processed signal having a value corresponding to said input signal value;
wherein said processed signal value represents one of a plurality of values which includes
said maximum sample signal value,
said minimum sample signal value,
a first one of said plurality of sample signal values, and
a combination of said first one and a second one of said plurality of sample signal values.

51. (CURRENTLY AMENDED) ~~The method of claim 45, wherein said generating, in response to said at least one control signal and said input signal, at~~

Atty. Docket No.: 03-019-US (10101.03.0190)- 24 -
CHICAGO/#1390143.1

10/685,787

PATENTAMENDMENT B (IN RESPONSE TO PAPER NO. 20050419
(OFFICE ACTION DATED JUNE 24, 2005))

~~least one sample signal having a plurality of sample signal values, including maximum and minimum sample signal values, and corresponding to said input signal value comprises: A method of data signal amplification and processing with multiple signal gains, comprising:~~

~~_____ receiving at least one control signal;~~
~~_____ receiving an input signal having an input signal value;~~
~~_____ generating, in response to said at least one control signal and said input signal, at least one sample signal having a plurality of sample signal values, including maximum and minimum sample signal values, and corresponding to said input signal value, by~~
~~_____ responding to one of said at least one control signal by providing a switched signal; signal; and~~
~~_____ responding to said switched signal by charging shunt capacitive circuitry to provide said at least one sample signal; signal; and~~
~~_____ receiving one or more processing control signals and in response thereto processing said at least one sample signal and generating a processed signal having a value corresponding to said input signal value;~~
~~_____ wherein said processed signal value represents one of a plurality of values which includes~~
~~_____ said maximum sample signal value,~~
~~_____ said minimum sample signal value,~~
~~_____ a first one of said plurality of sample signal values, and~~
~~_____ a combination of said first one and a second one of said plurality of sample signal values.~~

52. (CANCELLED)

53. (CURRENTLY AMENDED) The method of claim 52, wherein said

Atty. Docket No.: 03-019-US (10101.03.0190)- 25 -
CHICAGO/#1390143.1

10/685,787

PATENT

AMENDMENT B (IN RESPONSE TO PAPER NO. 20050419
(OFFICE ACTION DATED JUNE 24, 2005))

~~responding to another one or more of said one or more processing control signals~~
~~and said digital signal by generating said processed signal comprises:~~ A method of
data signal amplification and processing with multiple signal gains, comprising:

- receiving at least one control signal;
- receiving an input signal having an input signal value;
- generating, in response to said at least one control signal and said input
signal, at least one sample signal having a plurality of sample signal values,
including maximum and minimum sample signal values, and corresponding to said
input signal value; and
- receiving one or more processing control signals and in response thereto
processing said at least one sample signal and generating a processed signal having
a value corresponding to said input signal value, by
- responding to one of said one or more processing control signals by
converting said at least one sample signal to a digital signal having a plurality of
values corresponding to said plurality of sample signal values, and
- responding to another one or more of said one or more processing
control signals and said digital signal by generating said processed signal, by
- responding to said digital signal by comparing said plurality
of digital signal values to predetermined lower and higher thresholds; thresholds,
and
- responding to said digital signal by selectively combining
first and second ones of said plurality of digital signal values to generate a
combination signal corresponding to said combination of said first and second ones
of said plurality of sample signal values;
- wherein said processed signal value represents one of a plurality of values
which includes
- said maximum sample signal value,
- said minimum sample signal value,

Atty. Docket No.: 03-019-US (10101.03.0190)- 26 -
CHICAGO/#1390143.1

10/685,787

PATENT

AMENDMENT B (IN RESPONSE TO PAPER NO. 20050419
(OFFICE ACTION DATED JUNE 24, 2005))

a first one of said plurality of sample signal values, and
a combination of said first one and a second one of said plurality of
sample signal values.

54. (CANCELLED)

55. (CURRENTLY AMENDED) ~~The apparatus of claim 54, wherein:~~
~~said plurality of sample signal values includes maximum and minimum~~
~~sample signal values; and~~ An apparatus including data signal amplifier circuitry
with multiple signal gains, comprising:

sampling amplifier circuitry with a plurality of signal gains, including at
least maximum and minimum signal gains, and responsive to at least one control
signal and an input signal having an input signal value by providing at least one
sample signal having a plurality of sample signal values related to said plurality of
signal gains, corresponding to said input signal value and including maximum and
minimum sample signal values; and

processing circuitry coupled to said sampling amplifier circuitry and
responsive to said at least one sample signal and one or more processing control
signals by processing said at least one sample signal to provide a processed signal
having a value corresponding to said input signal value;

wherein said processed signal value represents

said first value when said maximum sample signal value fails to
traverse a predetermined lower threshold,

said second value when an adjacent larger one of said plurality of
sample signal values traverses a predetermined higher threshold,

said third value as a smaller of mutually adjacent ones of a pair of
said plurality of sample signal values when a larger one of said pair of sample
signal values traverses said predetermined higher threshold and said smaller value

Attr. Docket No.: 03-019-US (10101.03.0190)- 27 -
CHICAGO/#1390143.1

10/685,787

PATENT

AMENDMENT B (IN RESPONSE TO PAPER NO. 20050419
(OFFICE ACTION DATED JUNE 24, 2005))

fails to traverse said predetermined lower threshold, and
said fourth value as a combination of said smaller and larger ones of
said pair of sample signal values when said larger value traverses said
predetermined lower threshold and fails to traverse said predetermined higher
threshold.

56. (CANCELLED)

57. (CURRENTLY AMENDED) The apparatus of claim 54, An apparatus including data signal amplifier circuitry with multiple signal gains, comprising:

sampling amplifier circuitry with a plurality of signal gains, including at least maximum and minimum signal gains, and responsive to at least one control signal and an input signal having an input signal value by providing at least one sample signal having a plurality of sample signal values related to said plurality of signal gains and corresponding to said input signal value; and

processing circuitry coupled to said sampling amplifier circuitry and responsive to said at least one sample signal and one or more processing control signals by processing said at least one sample signal to provide a processed signal having a value corresponding to said input signal value;

wherein said processed signal value represents one of a plurality of values which includes

a first value corresponding to said minimum signal gain,

a second value corresponding to said maximum signal gain,

a third value corresponding to a first one of said plurality of signal gains, and

a fourth value corresponding to a combination of said first one and a second one of said plurality of signal gains; and

Atty. Docket No.: 03-019-US (10101.03.0190)- 28 -
CHICAGO/#1390143..1

10/685,787

PATENT

AMENDMENT B (IN RESPONSE TO PAPER NO. 20050419
(OFFICE ACTION DATED JUNE 24, 2005))

_____ wherein said sampling amplifier circuitry comprises:
_____ first amplifier circuitry including input and output terminals;
_____ a feedback capacitance coupled between said first amplifier
circuitry input and output terminals; and
_____ second amplifier circuitry coupled to said first amplifier circuitry
output terminal and having said variable signal gain responsive to at least one of
said at least one control signal.

58. (CANCELLED)

59. (CURRENTLY AMENDED) ~~The apparatus of claim 54,~~
~~wherein:~~ An apparatus including data signal amplifier circuitry with multiple signal
gains, comprising:
_____ sampling amplifier circuitry with a plurality of signal gains, including at
least maximum and minimum signal gains, and responsive to at least one control
signal and an input signal having an input signal value by providing at least one
sample signal having a plurality of sample signal values related to said plurality of
signal gains and corresponding to said input signal value; and
_____ processing circuitry coupled to said sampling amplifier circuitry and
responsive to said at least one sample signal and one or more processing control
signals by processing said at least one sample signal to provide a processed signal
having a value corresponding to said input signal value;
_____ wherein said processed signal value represents one of a plurality of values
which includes
_____ a first value corresponding to said minimum signal gain,
_____ a second value corresponding to said maximum signal gain,
_____ a third value corresponding to a first one of said plurality of signal
gains, and

Atty. Docket No.: 03-019-US (10101.03.0190)- 29 -
CHICAGO/#1390143.1

10/685,787

PATENT

AMENDMENT B (IN RESPONSE TO PAPER NO. 20050419
(OFFICE ACTION DATED JUNE 24, 2005))

a fourth value corresponding to a combination of said first one and a second one of said plurality of signal gains;

wherein said input signal has an input signal charge associated therewith;

and

wherein said sampling amplifier circuitry comprises

a signal node to convey said input signal,

capacitive circuitry, and

a switch coupled between said signal node and said capacitive circuitry, and responsive to one or more of said at least one control signal by conveying a predetermined portion of said input signal charge to said capacitive circuitry.

60. *(CURRENTLY AMENDED)* ~~The apparatus of claim 54. An~~
apparatus including data signal amplifier circuitry with multiple signal gains,
comprising:

sampling amplifier circuitry with a plurality of signal gains, including at least maximum and minimum signal gains, and responsive to at least one control signal and an input signal having an input signal value by providing at least one sample signal having a plurality of sample signal values related to said plurality of signal gains and corresponding to said input signal value; and

processing circuitry coupled to said sampling amplifier circuitry and responsive to said at least one sample signal and one or more processing control signals by processing said at least one sample signal to provide a processed signal having a value corresponding to said input signal value;

wherein said processed signal value represents one of a plurality of values which includes

a first value corresponding to said minimum signal gain,

a second value corresponding to said maximum signal gain.

Atty. Docket No.: 03-019-US (10101.03.0190)- 30 -
CHICAGO/#1390143.1

10/685,787

PATENT

AMENDMENT B (IN RESPONSE TO PAPER NO. 20050419
(OFFICE ACTION DATED JUNE 24, 2005))

a third value corresponding to a first one of said plurality of signal gains, and
a fourth value corresponding to a combination of said first one and a second one of said plurality of signal gains; and
_____ wherein said sampling amplifier circuitry comprises:
_____ serial switching circuitry responsive to one of said at least one control signal by providing a switched signal; and
_____ shunt capacitive circuitry coupled to said serial switching circuitry and responsive to said switched signal by charging to provide said at least one sample signal.

61. (CANCELLED)

62. (CURRENTLY AMENDED) ~~The apparatus of claim 61, An~~
apparatus including data signal amplifier circuitry with multiple signal gains, comprising:
sampling amplifier circuitry with a plurality of signal gains, including at least maximum and minimum signal gains, and responsive to at least one control signal and an input signal having an input signal value by providing at least one sample signal having a plurality of sample signal values related to said plurality of signal gains and corresponding to said input signal value; and
processing circuitry coupled to said sampling amplifier circuitry and responsive to said at least one sample signal and one or more processing control signals by processing said at least one sample signal to provide a processed signal having a value corresponding to said input signal value;
wherein said processed signal value represents one of a plurality of values which includes
a first value corresponding to said minimum signal gain,

Atty. Docket No.: 03-019-US (10101.03.0190)- 31 -
CHICAGO/#1390143.1

10/685,787

PATENT

AMENDMENT B (IN RESPONSE TO PAPER NO. 20050419
(OFFICE ACTION DATED JUNE 24, 2005))

a second value corresponding to said maximum signal gain,
a third value corresponding to a first one of said plurality of signal
gains, and
a fourth value corresponding to a combination of said first one and a
second one of said plurality of signal gains;
wherein said processing circuitry comprises
analog-to-digital conversion circuitry responsive to one of said one
or more processing control signals by converting said sample signal to provide a
digital signal having a plurality of values corresponding to said plurality of sample
signal values, and
computational circuitry coupled to said analog-to-digital conversion
circuitry and responsive to another one or more of said one or more processing
control signals and said digital signal by providing said processed signal; and
wherein said computational circuitry comprises:
comprises
comparison circuitry responsive to said digital signal by comparing
said plurality of digital signal values to predetermined lower and higher thresholds;
thresholds, and
combining circuitry responsive to said digital signal by selectively
combining first and second ones of said plurality of digital signal values to provide
a combination signal corresponding to said combination of said first and second
ones of said plurality of sample signal values.

63. (CANCELLED)

64. (CANCELLED)

65. (CURRENTLY AMENDED) ~~The method of claim 64, wherein:~~
~~said plurality of sample signal values includes maximum and minimum~~
~~sample signal values; and~~ A method of data signal amplification and processing

Atty. Docket No.: 03-019-US (10101.03.0190)- 32 -
CHICAGO/#1390143.1

10/685,787

PATENT

AMENDMENT B (IN RESPONSE TO PAPER NO. 20050419
(OFFICE ACTION DATED JUNE 24, 2005))

with multiple signal gains, comprising:

receiving at least one control signal:

receiving an input signal having an input signal value;

generating, in conformance with a plurality of signal gains, including at least maximum and minimum signal gains, and in response to said at least one control signal and said input signal, at least one sample signal having a plurality of sample signal values related to said plurality of signal gains, corresponding to said input signal value and including maximum and minimum sample signal values;

and

receiving one or more processing control signals and in response thereto processing said at least one sample signal and generating a processed signal having a value corresponding to said input signal value;

wherein said processed signal value represents

said first value when said maximum sample signal value fails to traverse a predetermined lower threshold,

said second value when an adjacent larger one of said plurality of sample signal values traverses a predetermined higher threshold,

said third value as a smaller of mutually adjacent ones of a pair of said plurality of sample signal values when a larger one of said pair of sample signal values traverses said predetermined higher threshold and said smaller value fails to traverse said predetermined lower threshold, and

said fourth value as a combination of said smaller and larger ones of said pair of sample signal values when said larger value traverses said predetermined lower threshold and fails to traverse said predetermined higher threshold.

66. (CANCELLED)

Atty. Docket No.: 03-019-US (10101.03.0190)- 33 -
CHICAGO/#1390143.1

10/685,787

PATENT

AMENDMENT B (IN RESPONSE TO PAPER NO. 20050419
(OFFICE ACTION DATED JUNE 24, 2005))

67. (CURRENTLY AMENDED) The method of claim 64, wherein said generating, in conformance with a plurality of signal gains, including at least maximum and minimum signal gains, and in response to said at least one control signal and said input signal, at least one sample signal having a plurality of sample signal values related to said plurality of signal gains and corresponding to said input signal value comprises: A method of data signal amplification and processing with multiple signal gains, comprising:

receiving at least one control signal;

receiving an input signal having an input signal value;

generating, in conformance with a plurality of signal gains, including at least maximum and minimum signal gains, and in response to said at least one control signal and said input signal, at least one sample signal having a plurality of sample signal values related to said plurality of signal gains and corresponding to said input signal value, by

generating an initial signal in response to said input signal with first amplifier circuitry including a feedback capacitance; capacitance, and

generating said at least one sample signal in response to said initial signal with second amplifier circuitry having a variable signal gain responsive to at least one of said plurality control signals; signals; and

receiving one or more processing control signals and in response thereto processing said at least one sample signal and generating a processed signal having a value corresponding to said input signal value;

wherein said processed signal value represents one of a plurality of values which includes

a first value corresponding to said minimum signal gain,

a second value corresponding to said maximum signal gain,

a third value corresponding to a first one of said plurality of signal gains, and

Atty. Docket No.: 03-019-US (10101.03.0190)- 34 -
CHICAGO/#1390143.1

10/685,787

PATENT

AMENDMENT B (IN RESPONSE TO PAPER NO. 20050419
(OFFICE ACTION DATED JUNE 24, 2005))

a fourth value corresponding to a combination of said first one and a second one of said plurality of signal gains.

68. (CANCELLED)

69. (CURRENTLY AMENDED) ~~The method of claim 64, wherein:~~
~~said input signal has A method of data signal amplification and processing with multiple signal gains, comprising:~~
~~receiving at least one control signal;~~
~~receiving an input signal having an input signal value and an input signal charge associated therewith; and~~
~~generating, in conformance with a plurality of signal gains, including at least maximum and minimum signal gains, and in response to said at least one control signal and said input signal, at least one sample signal having a plurality of sample signal values related to said plurality of signal gains and corresponding to said input signal value, by said generating, in conformance with a plurality of signal gains, including at least maximum and minimum signal gains, and in response to said at least one control signal and said input signal, at least one sample signal having a plurality of sample signal values related to said plurality of signal gains and corresponding to said input signal value comprises conveying a predetermined portion of said input signal charge, responsive to one or more of said at least one control signal, to capacitive circuitry; and~~
~~receiving one or more processing control signals and in response thereto processing said at least one sample signal and generating a processed signal having a value corresponding to said input signal value;~~
~~wherein said processed signal value represents one of a plurality of values which includes~~
~~a first value corresponding to said minimum signal gain.~~

Atty. Docket No.: 03-019-US (10101.03.0190)- 35 -
CHICAGO/#1390143.1

10/685,787

PATENT

AMENDMENT B (IN RESPONSE TO PAPER NO. 20050419
(OFFICE ACTION DATED JUNE 24, 2005))

a second value corresponding to said maximum signal gain,
a third value corresponding to a first one of said plurality of signal
gains, and
a fourth value corresponding to a combination of said first one and a
second one of said plurality of signal gains.

70. (CURRENTLY AMENDED) ~~The method of claim 64, wherein said~~
~~generating, in conformance with a plurality of signal gains, including at least~~
~~maximum and minimum signal gains, and in response to said at least one control~~
~~signal and said input signal, at least one sample signal having a plurality of sample~~
~~signal values related to said plurality of signal gains and corresponding to said~~
~~input signal value comprises:~~ A method of data signal amplification and processing
with multiple signal gains, comprising:

receiving at least one control signal;
receiving an input signal having an input signal value;
generating, in conformance with a plurality of signal gains, including at
least maximum and minimum signal gains, and in response to said at least one
control signal and said input signal, at least one sample signal having a plurality of
sample signal values related to said plurality of signal gains and corresponding to
said input signal value, by
responding to one of said at least one control signal by providing a
switched signal; signal, and
responding to said switched signal by charging shunt capacitive
circuitry to provide said at least one sample signal; signal; and
receiving one or more processing control signals and in response thereto
processing said at least one sample signal and generating a processed signal having
a value corresponding to said input signal value;
wherein said processed signal value represents one of a plurality of values

Atty. Docket No.: 03-019-US (10101.03.0190)- 36 -
CHICAGO/#1390143.1

10/685,787

PATENT

AMENDMENT B (IN RESPONSE TO PAPER NO. 20050419
(OFFICE ACTION DATED JUNE 24, 2005))

which includes

- a first value corresponding to said minimum signal gain,
- a second value corresponding to said maximum signal gain,
- a third value corresponding to a first one of said plurality of signal gains, and
- a fourth value corresponding to a combination of said first one and a second one of said plurality of signal gains.

71. (CANCELLED)

72. (CURRENTLY AMENDED) ~~The method of claim 71, wherein said responding to another one or more of said one or more processing control signals and said digital signal by generating said processed signal comprises:~~ A method of data signal amplification and processing with multiple signal gains, comprising:

- receiving at least one control signal;
- receiving an input signal having an input signal value;
- generating, in conformance with a plurality of signal gains, including at least maximum and minimum signal gains, and in response to said at least one control signal and said input signal, at least one sample signal having a plurality of sample signal values related to said plurality of signal gains and corresponding to said input signal value; and
- receiving one or more processing control signals and in response thereto processing said at least one sample signal and generating a processed signal having a value corresponding to said input signal value, by
- responding to one of said one or more processing control signals by converting said at least one sample signal to a digital signal having a plurality of values corresponding to said plurality of sample signal values, and
- responding to another one or more of said one or more processing

Att. Docket No.: 03-019-US (10101.03.0190)- 37 -
CHICAGO/#1390143.1

10/685,787

PATENT

AMENDMENT B (IN RESPONSE TO PAPER NO. 20050419
(OFFICE ACTION DATED JUNE 24, 2005))

control signals and said digital signal by generating said processed signal by
_____ responding to said digital signal by comparing said plurality
of digital signal values to predetermined lower and higher thresholds; thresholds,
and
_____ responding to said digital signal by selectively combining
first and second ones of said plurality of digital signal values to generate a
combination signal corresponding to said combination of said first and second ones
of said plurality of sample signal-values; values;
wherein said processed signal value represents one of a plurality of values
which includes
_____ a first value corresponding to said minimum signal gain,
_____ a second value corresponding to said maximum signal gain,
_____ a third value corresponding to a first one of said plurality of signal
gains, and
_____ a fourth value corresponding to a combination of said first one and a
second one of said plurality of signal gains.

Atty. Docket No.: 03-019-US (10101.03.0190)- 38 -
CHICAGO/#1390143.1